

Wachendorff Automation GmbH & Co. KG

Industriestraße 7 • D-65366 Geisenheim

Tel.: +49(0)6722/9965-25 • Fax: +49(0)6722/9965-70

support-wa@wachendorff.de • www.wachendorff-automation.com

Installation Kit for frequency-control lifts WDGAS58B with shaft encoder



The following installation kits are available for fitting the encoder to a frequency controlled lift. Every installation kit consists:

1 x Encoder, 1 x Mountingangle, 1 x shielded cable 15 m length,

1 x double loop coupling, 1 x Shaftadapter

Mechanical Data

Housing

- Clamping flange: Aluminium

- Cap: Aluminium, powder coated

- Diameter: 58 mm

Shaft

Material: stainless steel
Diameter: 10 mm, H7
Lenght: 20 mm
Permitted load max. 220 N radial

Load: max. 120 N axial

- Starting torque: approx. 1 Ncm at ambient temperature

Bearings

- Type: 2 precision ball bearings

- Service life: 1x 10° U revs. at 100 % shaft load 1x 10° U revs. at 40 % shaft load

1x 1011 revs. at 20 % shaft load

Max. operating speed: 8000 rpm

Weight: approx. 250 g

Connections: SH8: radial connector, 8 pin

Operating temperature: -20 °C up to +80 °C Storage temperature: -30 °C up to +80 °C

Machinery Directive: basic data safety integrity level

MTTF_d: 200 a Mission time (T_M) : 25 a

Nominale service life 1x 10¹¹ revs. at 8000 rpm and (L₁oh): 20 % rated shaft load

Diagnostic coverage (DC): 0 %

Encoder-Order No.: WDGI58B-YYYY-ABN-H24-SH8

- YYYY: with 1024, 2048, 4096 PPR - 3 channels, A, B and zero marker pulse N

- H24: 10 VDC up to 30 VDC HTL

Power supply

- SH8: radial connector, 8 pin

WDGI58B-YYYY-ABN-R05-SH8

- YYYY: mit 1024, 2048, 4096 PPR

- 6 channels, A, B, zero marker pulse N and inv.

- 5 VDC TTL power supply with inv.

output circuit

- SH8: radial connector, 8 pin

YYYY: Please specify required. PPR: 1024, 2048 or 4096

Pin identification SH8

IIIL FINITE	-
2	
1	
3	
6	The
4	of
7	100
5	the
8	end
	1 3 6 4 7 5




The view of the soldered side of the connector connector corresponds to the view of the pin arrangement on the

encoder.

- · Complete retrofit set
- · Quickly and reliably fitted with the aid of the accessories
- Cost-effective modernisation solution
- TTL, HTL output
- Threads: M8, M10, M12, M16 und M20


www.wachendorff-automation.com/wdgas58b



(in use with shaft adapter M8)

Mounting bracket:


The mounting bracket makes for easy installation of the encoder in the lift system. However care should be taken that the admissible load of the coupling is adhered to.



Order No.: MW58B

Cable:

The cable is 15 m in length and is shielded, however the shield is not connected to the connector housing. With a mated connector, the encoder meets protection class IP40.



The cable has a connection as follows:

Function Colour Positive brown Negative white green Α A inv. red R vellow B inv. black Ν gray N inv. violet Shield: cable braiding

Order No. KD84015



Double loop coupling:

The double loop coupling serves to compensate for any mis-alignment between the drive and the encoder. The coupling has extremely high compensation capabilities.

Features: excellent compensation capabilities

Max. offset of shafts: axial: max. ±4 mm


radial: max. ±3 mm angular: ± 12°

3000 rpm Max. operating speed: Starting torque: max. 200 Ncm

Material:

- Hub: zinc-plated - Compensating element: polyurethan Weight: 85 g

DIN 916 M4x6 (4x) Fixing: -30 °C up to +80 °C Operating temperature:




Shaft adapters




Shaft adapters:

The shaft adapters are screwed into an appropriate thread on the lift and allow a simple connection via the double loop coupling.




Shaft adapter M8



Order No.: WDGWA10M08

Order No.: WDGWA10M10


Shaft adapter M10



Shaft adapter M12

1x45°

60




Shaft adapter M16



Order No.: WDGWA10M20

SW30



40

85

Shaft adapter M20

XX: Please insert the code corresponding to the required shaft adapter:

Shaft adapter 10/M8: Shaft adapter 10/M10: 10 Shaft adapter 10/M12: 12 Shaft adapter 10/M16: 16 Shaft adapter 10/M20: 20

YYYY: Please specify required. PPR: 1024, 2048 or 4096

Ordering information WDGAS58B:

Description:	Order No.:
Installation Kit 10 VDC - 30 VDC HTL comprising: - WDGI58B-10-YYYY-ABN-H24-SH8 - YYYY: with 1024, 2048, 4096 PPR - 3 channels, A, B, N - H24: 10 - 30 VDC Power supply - SH8: radial connector, 8 pin - MW58B - KD84015: 15 m ready-made shielded cable - DSK481010 - XX: Shaft adapter: 08, 10, 12, 16 or 20	WDGAS58BYYYYH24XX
Installation Kit 5 VDC TTL, RS422 comprising: - WDGI58B-10-YYYY-ABN-R05-SH8 - YYYY: with1024, 2048, 4096 PPR - 6 channels, A, B, N, Ā, B, N - R05: 5 VDC TTL power supply with inv. output circuit - SH8: radial connector 8 pin - MW58B - KD84015: 15 m ready-made shielded cable - DSK48101 - XX: Shaft adapter: 08, 10, 12, 16 or 20	WDGAS58BYYYYR05XX

Customs tariff number: 90318020 Country of origin: Germany